

6165 W Detroit St. • Chandler AZ 85226
+1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
www.crafco.com

READ BEFORE USING THIS PRODUCT

GENERAL

Action Pave Acrylic Textured White Line Paint is an extremely durable, 100% acrylic emulsion fortified with fine silica. Action Pave Acrylic Textured White Line Paint is specially formulated for use on many indoor and outdoor athletic and recreational surfaces. Action Pave Acrylic Textured White Line Paint offers neat, clean, permanent line markings. Action Pave Acrylic Textured White Line Paint is designed to be applied over all other Action Pave Acrylic surfaces or uncoated asphalt surfaces. Action Pave Acrylic Textured White Line Paint is not for use on untreated concrete surfaces

Recommended Uses

Action Pave Acrylic Textured White Line Paint is used for Line and Event markings for sport courts including, but not limited to, basketball, hockey/in-line skating, pickleball, playground, running surface, shuffleboard, tennis and multi-purpose courts. Action Pave Acrylic Textured White Line Paint is part of the Action Pave Sport Court System that may include resurfacer, cushion, filler, finish, and line striping.

Technical Data

Following is the technical data for Action Pave Acrylic Textured White Line Paint

Property	Test Method	Technical Data
VOC	Calculated	100 g/L maximum
Rotational Viscosity, 77 °F, 20 RPM	Brookfield	23,000 ± 5000
Density, lb/gal	ASTM 1475	11.7 ± 0.5
pH	-	8.5 to 9.5

Installation Instructions

Action Pave Acrylic Textured White Line Paint is to be applied over surfaces which have already received **Action Pave Acrylic coatings** or uncoated asphalt surfaces. New asphalt pavement shall cure a minimum of 14 days before applying **Action Pave**. Not for use on untreated concrete surfaces. The surface must be clean and free of grease, oil, and any other foreign material. Action Pave Acrylic Textured White Line Paint is applied with a paint brush, roller, or other suitable paint application equipment. Clean equipment with water immediately after use.

- Approximately one-gallon **Action Pave Acrylic Textured White Line Paint** is required for a standard double's tennis court. 500 lin. ft. @ 2" wide, per gallon (1 gal. generally required for one double's tennis court, 481 in. ft. with 2 in. wide lines). Uncoated asphalt surfaces may require two coats when striping. Do not apply over coal tar emulsions.

Limitations

- Do not apply Action Pave Acrylic Textured White Line Paint when the surface temperature is below 50 °F (10 °C) or when surface temperature is above 130 °F (55 °C).
- Do not apply when rain, fog or high humidity is imminent.

Packaging and Availability

5 Gal. (18.9 L) pails, and 1 Gal. (3.7 L) pails.

Storage

- Close cover tightly.
- Do not store in direct sunlight.
- Keep from freezing.
- Storage temperature range 40 – 90 °F.
- Dispose of container in accordance with state and federal regulations.



PRODUCT DATA SHEET

**ACTION PAVE®
ACRYLIC TEXTURED WHITE LINE PAINT**

Part No. 11481WL

FEBRUARY 2022

6165 W Detroit St. • Chandler AZ 85226
+1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
www.crafco.com

WARRANTY

ACTION PAVE® Acrylic Textured White Line Paint is warranted by the manufacturer to meet specification requirements at time of shipment. Techniques used for pavement preparation prior to Action Pave Acrylic Textured Acrylic White Line Paint application are beyond manufacturer control as are use and application of acrylic coating; therefore, the manufacturer shall not be responsible for improperly applied or misused Action Pave Acrylic Textured White Line Paint. Remedies against the manufacturer are limited to replacing nonconforming product or refund (full or partial) of purchase price. All claims for breach of this warranty must be made within three (3) months of delivery date. There shall be no other warranties expressed or implied. **For optimum performance, follow recommendations for Action Pave Acrylic Installation Instructions.**

No informal dispute mechanism has been established. Notice must be given in writing to Crafco, Inc 6165 W. Detroit St., Chandler, AZ 85226. A sample of the product claimed defective must be retained together with satisfactory proof of purchase. No claim will be honored if the lot number(s) are not provided therewith. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES AND EXPRESSLY EXCLUDES ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR PARTICULAR PURPOSE, AS WELL AS LIABILITY FOR CONSEQUENTIAL DAMAGES. Crafco Sales or Technical Representatives have no authority to extend any guarantee beyond that outline above.